



FASTASEAL 3528 Clear Sealer

FASTASEAL 3030 is a clear fast drying single pack sealer.

Product Advantages

- Easy to sand and has excellent adhesion to all timber species
- Efficient isolator to wax extraction problems
- Fast drying product reducing down time between coats
- Excellent flow and levelling results in smooth finish
- Helps keep timber light coloured and closer to its natural appearance

Typical Applications

Interior use only. Timber, particleboard or cork flooring.

Product Properties

Build:	Sealer
Sandability:	Excellent
Solvent Resistance:	Sealer
Water Resistance:	Sealer
Levelling & Flow:	Excellent

Typical Properties

Colour:	Milky
Gloss:	Sealer

Product Approvals

FASTASEAL 3528 has been evaluated for AS/NZS 4586:2004: Slip resistance classification of new pedestrian surface materials by Advanced Technology Testing & Research (ATTAR). The coating system passed the requirements of the "Dry Slip Resistance" and was classified as Dry = F. Certificates available on request.

Coverage:

Base coat: Timber, Parquetry Floors
Cork & Particleboard – 12-15 m² per litre

Subsequent coats:

Coverage is dependent upon the porosity of the substrate.

Thinning:

Not normally required but, if desired, add up to 5% Thinners 1210 or in hot weather add up to 3% Wet Edge Extender 1211.

Application Methods:

6mm mohair roller or high quality brush.

Drying: Allow 30 minutes to 1 hour to dry before sanding.

Low temperatures and heavy film thickness will retard drying times. Direct sunlight and draft during drying may affect the final gloss level of the coating.

Recommended Sealers: FASTASEAL 3528 is a sealer

Application Equipment Clean Up: Clean all equipment using Brush Cleaner 3321. Ensure all cleaning solvents are removed before placing equipment back in the coating.

Shelf Life: 12 months, see label for use by date.

Packaging: 20 litres

Refer to the DURAPOL Product Information Guide for more information.

Health & Safety

Before handling, refer to the Material Safety Data Sheet for health and safety information. Ensure that all personnel using this product have read and understood this data sheet and the associated MSDS and packaging label before using this product.

Note: Coatings give off strong solvents and odours during the drying process. People and pets should be removed from the building during the application and drying of coatings. All food and fabrics should also be removed to reduce the risk of them becoming tainted during the drying process.

Mirotone Pty Ltd Australia (Head Office)
ABN 40 000 041 136
21 Marigold Street,
Revesby NSW 2212 Australia
P +61 2 9795 3700 F +61 2 9771 3601
sales@mirotone.com.au

Mirotone (NZ) Ltd New Zealand (Head Office)
32 Cryers Road, East Tamaki
Auckland 2013, New Zealand
P 0800 34 64 74 F 0800 34 64 34
information@mirotone.co.nz

Mirotone (Thailand) Co., Ltd
83 Moo 4, Poochaosamingprai Rd,
Samrong Klang, Prapadaeng,
Samutprakam, 10130, Thailand
P +66 2 754 4451 F +66 2 754 4450

www.mirotone.com